



SB-E varnished



Product description:

SB-E is a threaded elbow made of rolled mild steel, baked finish, in black varnish, threaded at both ends, one screwed-on coupling (SM-E).

This threaded elbow is used for joining Staro Gewinde-ES varnished steel conduits. Advantages are its very heavy compressive strength and extreme temperature resistance.



VDE 0605
DIN EN 61386-21
classification: 555611
minimum compressive strength: 4000 N/5 cm



Cat. No.:	Type	Inside Ø mm	Outside Ø mm	Content	PU	Weight PU/kg	Thread	Bend radius
202 60 016	16	12,7	16	15	PCS	1,680	M16x1,5	55
202 60 020	20	16,3	20	25	PCS	4,875	M20x1,5	80
202 60 025	25	21,3	25	25	PCS	7,525	M25x1,5	110
202 60 032	32	28,2	32	20	PCS	9,240	M32x1,5	140
202 60 040	40	36,2	40	15	PCS	11,115	M40x1,5	170
202 60 050	50	46,2	50	5	PCS	5,700	M50x1,5	190
202 60 063	63	58,7	63	3	PCS	5,835	M63x1,5	220

Standardisation

EN 61386-1:2009 Conduit systems for cable management - Part 1: General requirements / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

EN 61386-21:2011 Conduit systems for cable management - Part 21: Particular requirements - Rigid conduit systems / Source: Official Journal of the European Union of 16 May 2014 / Applied in full

Outside diameter according to DIN EN 60423 / IEC 60423

All dimensions without tolerances are for information only.

FRÄNKISCHE ROHRWERKE Gebr. Kirchner GmbH & Co. KG | Hellinger Str. 1 | 97486 Königsberg/Bayern
Hotline +49 9525 88-8123 | Fax +49 9525 88-2151 | info.elektro@fraenkische.com | www.fraenkische.com

Subject to change without notice.

Page 1 of 2

Last modified: 30.05.17



SB-E varnished

Material properties			Fields of application		
Zero halogen	DIN VDE V 0604-2-100		on plaster	• machines	•
Low smoke	DIN EN 61034-2		under plaster	• hot asphalt	•
Non-flame propagating	DIN EN 61386-1	•	on wood	• under screed	•
UV-resistant	DIN 53387		underground installation	prefabricated construction	•
Highspeed			in concrete	• outdoor	

Chemical properties	
Resistant to	fats, oil and most oil additives contained therein
Limitedly resistant to	neutral to slightly alkaline substances
Not resistant to	acids

Risk analysis

The product has been manufactured and tested according to the harmonized standards 61386-1 and 61386-21 in the sense of harmonization legislation of the EU. All safety-relevant tests have been adhered to. This product poses no further risk.

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.

Information can be obtained from our technical consultants at +49 9525 88-8123

