

Road and track drainage Shaft systems

StrabuControl® Flushing and inspection shaft

PE-HD flushing and inspection shaft; as shaft, wye shaft or cross shaft; inside diameter of base body greater than 500 mm; colour: black



Technical data		
Application:	Flushing and inspection shaft for StormPipe and Strabusil drainage pipes for all fields of civil engineering and road engineering. Can be directly connected to StormPipe and Strabusil pipes using sealing rings.	
Material / raw material:	PE-HD (polyethylene)	
Specification:	Design as shaft (180°), wye shaft (90°) and cross shaft	
Shaft variants / nominal connection diameters:	Shaft: 2/250 Wye shaft: 3/250, 3/350 Cross shaft: 4/250, 4/350	2/400 - - - -
Effective height: [m]	0.70	0.80
Total height: [m]	0.75	0.85
Inside diameter of base body: [m]	> 0.50	> 0.50
Weight: [kg]	≤ 12	≤ 12
Technical characteristics:	Monolithic base body without weld seams; UV-resistant; resistant to acids, bases, oils, greases and cement according to DIN 8075; extremely durable and hard-wearing; high impact strength; nominal diameters DN 100, DN 150, DN 200 and DN 300 can be connected using reducers; extension pipe can be cut to length; with integrated compensating area; installation in traffic areas possible; watertight connection of pipes according to DIN 4262-1 possible	
Miscellaneous:	CAD library and CAD details Project shafts according to order form For accessories, see price catalogue and product documentation "Shaft systems for road drainage"	



www.fraenkische.com